Farbex

Antiseptic for mineral surfaces, concentrate 1:4



- it penetrates deeply into the base surface
- it reliably protects against bacteria, mould, and fungi



Sphere of application

Concentrated waterborne product is intended for treating of concrete, brick, stuccos, stone, asbestos concrete and other mineral and wooden surfaces. It disinfects and prevents mould, fungi, algae and other biological damages on the absorbing surfaces before undercoating and coating. It is especially recommended for wet spaces and poor aired spaces.

😑 Technical data

Consumption standard of 1 layer	100-125 ml/m ²
Thinner	Water. The antiseptic is ready to use. If necessary, dilute as recommended.
Application	Apply with a brush, a roller or a spraying gun.
Density (DSTU ISO 2811-1)	$\approx 1 \text{ g/cm}^3$
Drying period (23 °C, 50% RH)	•
Warranty period	24 months
Packaging	1,2,51
Color	colorless.

Composition

Water, biocide additive.

Application instruction



Using

- Clean the surface of dust, dirt, mould, fungi, putty, old paint, other coatings.
- For treating of wooden surfaces and causality prophylaxis of mineral surfaces, the antiseptic must be diluted with water in the ratio: 1 part of the antiseptic to 4 parts of water. In case of severe damage, it is not recommended to dilute the antiseptic.
- $\circ~$ The product is applied in 2 layers with a total consumption of less than 200 ml/m2.
- Add 80-100 ml of a solid antiseptic per 1 kg to waterborne paints, primers or chalk and cement mortars. Add antiseptic gradually
 thoroughly stirring. Before mixing the antiseptic with a solution, it is necessary to check their compatibility in a small amount.
 Clots and other signs of coagulation are not allowed.
- $\circ~$ Stir the antiseptic thoroughly before use.
- $\circ\;$ Apply with a brush, a roller, a sponge or a spraying gun.
- $\circ\;$ Treat the surfaces, that are often in contact with moisture, with special thoroughness.
- Drying period of one layer of the product (23 ° C; 50% RH) 1 hour. Apply each next layer with intervals of 1-2 hours, depending on the material of the surface.
- $\circ~$ Apply product at air and surface temperatures from + 5 °C to + 35 °C.
- Wash tools with water after finishing work.
- $\circ~$ When the surface, treated with the antiseptic, is completely dry it can be coated with any paint product.

Tool cleaning



POLYSAN MANUFACTURING COMPANY -

POLYSAN MANUFACTURING COMPANY MC «POLYSAN» LTD Ukraine, Sumy, I.Piddubnoho str. 25 tel./fax: +38 (0542) 650 621 www.farbex.ua



TECHNICAL DATA SHEET 13.12.2023

Farbex

SAFETY

Do not mix with other products and (or) organic solvents! Store in tightly closed original containers at the temperature from + 5 °C till + 35 °C. Keep out of moisture, direct sunlight, frost and out of reach of children. It retains its protective properties during short-term freezing and thawing. Use personal safety gear (special clothes, rubber gloves, respirator and safety glasses) If the application is performed indoors it is necessary to provide effective ventilation. If skin, eyes, or mucosa contact, rinse with plenty of water. Consult a doctor if necessary. More detailed information you can read from the safety data sheet. The product has a sanitary-epidemical conclusion of the state expertise.

💦 ENVIRONMENTAL PROTECTION

Do not empty into drains, ponds and in soil! Liquid rests shall be delivered to the waste drop-off point. Rests of dry products and empty containers shall be recycled as common construction waste, in accordance with the Law.

The authenticity of this information is based on laboratory tests and practical knowledge. The quality of the product completely corresponds to the demands of TU U 24.6 – 32318370-005:2007. As a manufacturer, the company isn't responsible for the damage caused by application, which is not in accordance with the directions. The applicability of the product for specific purposes shall be defined entirely by the consumer. Current information loses validity with the issue of a new edition.

