

Antiseptic for wooden surfaces

Specification

- it penetrates deeply into a timber
- it is intended for the treatment of wet timber
- it doesn't change the color of the wood



Sphere of application

Waterborne product with antiseptic properties is intended for eliminating and preventing of forming of fungi, mould and rot of the timber and wooden constructions for living, industrial and farming use. It can be applied prior to the coating with paint products and also as a single treatment of the wood. It is for external and internal use. Do not use antiseptic as a finishing coat for external works.

Technical data

Consumption standard of 1 layer	100-125 ml/m ²
Thinner	Water. The antiseptic is ready to use and does not require dilution.
Application	Apply with a brush, a roller or a spraying gun.
Density (DSTU ISO 2811-1)	≈ 1 g/cm ³
Drying period (23 °C, 50% RH)	-
Warranty period	24 months
Packaging	1 l, 2 l, 5 l, 10 l
Color	colorless.

Composition

Water, biocide additive.

Application instruction

1 Preliminary preparation

2 Using

- Clean the surface from dust, dirt, mould, fungi to the base surface.
- The solution shall be applied with a brush, a roller, a sponge or a spraying gun.
- The treatment shall be done in 2-3 applications, the total rate of product consumption - from 250 ml/m² to 300 ml/m² depending on the type of the surface.
- The drying period of each application (23 ° C; 50% RH) is 1 hour. Depending on the base, the next layers should be applied with an interval of 2 hours.
- Application shall be performed at air and surface temperature from + 5 °C to + 35 °C.
- Wash the tools with water after you finish the work.
- Apply paint products only after the surface, treated with the antiseptic, is completely dry.

3 Tool cleaning



SAFETY

Do not mix with other products and (or) organic solvents! Keep in the places out of reach of children in tightly closed original containers at the temperature from +5 °C till +35 °C. Keep out of moisture, direct sunlight and frost. During application use personal safety gear (work clothes, rubber gloves, a respirator and safety glasses). If the application is indoors well-arranged ventilation shall be provided. If skin, eye and mucosa contact, rinse with plenty of water. Consult a doctor if necessary. More detailed information you can read in the safety data sheet. The product has a sanitary-epidemical conclusion of the state expertise.

ENVIRONMENTAL PROTECTION

Do not empty into drains, ponds and in soil! Liquid rests shall be delivered to the waste drop-off point. Rests of dry products and empty containers shall be recycled as common construction waste, in accordance with the Law.

The authenticity of this information is based on laboratory tests and practical knowledge. The quality of the product completely corresponds to the demands of TU U 24.6 – 32318370-005:2007. As a manufacturer, the company isn't responsible for the damage caused by application, which is not in accordance with the directions. The applicability of the product for specific purposes shall be defined entirely by the consumer. Current information loses validity with the issue of a new edition.

