

Decorative wax for venetian stucco Cera Lavabile

Specification

It is a ready-to-use product for the product "Stucco Veneziano" TM Maxima. It gives the surface an additional decorative effect of polishing marble. It can be polished to the mirror effect. It also protects against damages and moisture effect.



Sphere of application

It is intended for protective coating on the surface of "Stucco Veneziano" TM Maxima. For interior works

Technical data

Thinner	Water
Application rate	18 g/m ² depending on the technique of application and quantity of coats
Drying period (20 °C, 60% RH)	6-12 hours. Drying period increases if the temperature is getting down and relative air humidity increases.
Resistance to static effect of water	less than 24 hours at 20 °C
Application	a trowel
Density (DSTU ISO 2811-1)	0,97 g/cm ³
Solids content (DSTU ISO 3251)	less than 30%
Warranty period	18 months from the date of manufacturing
Color	

Composition

Wax emulsions, additives.

Tinting

The product is tinted manually with pigment concentrate "Farbex Color", other tinting pastes or with a tinting machine according to NCS color rate and others.

It is recommended to use the product of one batch to avoid differences in color. Mix the product of different batches before use.

Slight deviations in technical properties are allowed after tinting.

Application instruction

1 Surface preparation

The surface shall be clean, dry and hard. Decorative base surface shall be completely dry.

2 Priming

Decorative acrylic surfaces (plasters and coats) need no preliminary undercoating.

3 Applying

Mix the wax thoroughly before use.

Apply the wax with a trowel. It shall be polished with wool cloth or a trowel till it completely dry.

Perform the works at the temperature of air and surface from +10°C till + 30°C and air humidity less then 80%.

4 Tool cleaning

Wash the tools with water after the work is finished. Don't let it dry. Rests of rejected product can be removed mechanically.

SAFETY

Do not mix with other products and (or) solvents! Store in tightly closed original containers at the temperature from +5 °C till +35 °C, preventing moisture effect, direct sunlight and frost, in the places out of reach of children. Use individual safe gear (special clothes, rubber gloves, respirator and protective glasses) during application works. Effective ventilation is necessary if applying indoors. If skin contact, wash thoroughly with water and soap. If eye contact, what with plenty of running water. Contact a doctor if necessary. VOC content is A/12 (WB): < 200 g/l. Actual VOC content is \leq 5 g/l. More precise information is in MSDS. The product has a sanitary-epidemical conclusion of the state expertise.

ENVIRONMENTAL PROTECTION

Do not empty into drains, ponds and in soil ! Liquid rests shall be delivered to the waste drop-off point. Rests of dry products and empty containers shall be recycled as common construction waste, in accordance with the Law.