Universal Enamel



Specification

*

Sphere of application

*

Technical data

	*
Density (DSTU ISO 2811-1)	ab. 0,9 g/cm^3
Viscosity (GOST 8420)	10-13 s
	min. 97 %
Drying period (DSTU ISO 9117-5)	max. 30 min
Adhesion	1
Warranty period	
Packaging	
Color	beige RAL 1001, white RAL 9010, yellow RAL 1023, green RAL 6029, red RAL 3020, silver RAL 9006, grey RAL 7046, dark blue RAL 5002, dark brown RAL 8017, black RAL 9005.
Gloss	glossy, matt.

Composition

*

Application instruction

1 Surface preparation

*

2 Applying

*

SAFETY

*

ENVIRONMENTAL PROTECTION

*

The authenticity of this information is based on laboratory tests and practical knowledge. The quality of the product completely corresponds to the demands of TU U 24.3-2370700019-001:2005. As a manufacturer, the company isn't responsible for the damage caused by application, which is not in accordance with the directions. Applicability of the product for specific purposes shall be defined entirely by the consumer. Current information loses validity with the issue of a new edition.

MC «POLYSAN» LTD
Ukraine, Sumy, I.Piddubnoho str. 25
tel./fax: +38 (0542) 650 621
www.farbex.ua