

Deep penetration silicone primer "Urban Primer"

Specification

- it penetrates deeply and hardens the base surface
- it lessens water permeability of the base surface without significant effect to vapor permeability of a complex coating.



Sphere of application

It is intended for improving adhesion, hardening and leveling of absorption of different surfaces (bricks, concrete, slag block, concrete stuccos, chip wood boards, MDF, gypsum boards and other porous surfaces) before performing of any finishing works with a plaster or putty, coating with acrylic or silicon waterborne products inside and outside.

Technical data

| | |
|---------------------------------|---|
| Consumption standard of 1 layer | 80-125 g/m ² , it depends on condition and structure of the surface. |
| Thinner | Water |
| Application | It is applied with a roller, a brush or a spraying gun. |
| Drying period (23 °C, 50% RH) | 1 hour. Drying period increases if the temperature is getting down and relative air humidity is increasing. |
| Solids content (DSTU ISO 3251) | 6±1 % |
| Density (DSTU ISO 2811-1) | ≈ 1 g/cm ³ |
| VOC content (ISO 11890) | < 15 g/l |
| Warranty period | 18 months from the date of manufacturing (at the temperature from +5 °C till +35 °C) |
| Packaging | 2 L, 10 L (2 kg, 5 kg, 10 kg) |
| Color | colorless. |

Composition

Acrylic dispersion, silicone emulsion, water, additives.



Application instruction

*

1 Surface preparation

*

2 Applying

*

3 Tool cleaning

*

SAFETY

Do not mix with other products and (or) organic solvents! Keep in the places out of reach of children in tightly closed original containers at the temperature from +5 °C till +35 °C. Keep out of moisture, direct sunlight and frost. During application use personal safety gear (work clothes, rubber gloves, a respirator and safety glasses). If application is indoors well-arranged ventilation shall be provided. If skin contact, wash thoroughly with water and soap. If eye contact, rinse with plenty of running water. Consult a doctor if necessary. VOC content: cat. A/h (WB): < 30 g/l. Actual VOC content ≤ 15 g/l. More detailed information you can read in the safety data sheet. The product has a sanitary-epidemic conclusion of the state expertise.

ENVIRONMENTAL PROTECTION

Do not empty into drains, ponds and in soil! Liquid rests shall be delivered to the waste drop-off point. Rests of dry products and empty containers shall be recycled as common construction waste, in accordance with the Law.

The authenticity of this information is based on laboratory tests and practical knowledge. The quality of the product completely corresponds to the demands of TU U 20.3-32318370-017:2018. As a manufacturer, the company isn't responsible for the damage caused by application, which is not in accordance with the directions. Applicability of the product for specific purposes shall be defined entirely by the consumer. Current information loses validity with the issue of a new edition.

