

Panel acrylic varnish

Specification

For interior work. Forms a strong elastic film. Reliably protects the surface, preserves its natural color and texture. The coating is resistant to wet cleaning and dirt. Has high adhesion to the bases. Dries quickly, does not have a pungent odor and is easy to apply.



Sphere of application

Designed for decorative protection of various wooden and mineral surfaces indoors, such as: "lining", skirting boards, natural wood panels, plywood, chipboard, fiberboard, MDF, brick, decorative stone, concrete, plaster, putty, etc. Do not use for varnishing floors and furniture!

Technical data

Consumption standard of 1 layer	
Thinner	
Application	
Drying period (23 °C, 50% RH)	
Gloss (DSTU ISO 2813)	
Hardness (DSTU ISO 1522)	
Solids content (DSTU ISO 3251)	
Density (DSTU ISO 2811-1)	
Warranty period	
Packaging	
Color	colorless.
Gloss	glossy.

Composition

Acrylic dispersion, water, targeted additives.

Application instruction

- /
- 1 Surface preparation
- /
- 2 Priming
- /
- 3 Applying of finishing layer
- /
- 4 Tool cleaning
- /



 SAFETY

/  ENVIRONMENTAL PROTECTION

Do not empty into drains, ponds and in soil ! Liquid rests shall be delivered to the waste drop-off point. Rests of dry products and empty containers shall be recycled as common construction waste, in accordance with the Law.

The authenticity of this information is based on laboratory tests and practical knowledge. The quality of the product completely corresponds to the demands of TU U 24.3-32318370-009:2011. As a manufacturer, the company isn't responsible for the damage caused by application, which is not in accordance with the directions. The applicability of the product for specific purposes shall be defined entirely by the consumer. Current information loses validity with the issue of a new edition.

