

Solvent 647

Specification

- it allows to keep the paint product of necessary viscosity
- it evaporates from a paint product at common temperature of the air
- does not contain precursors



Sphere of application

Designed for dissolving natural and synthetic resins, nitro varnishes, nitro enamels and other paint and varnish materials, in particular when painting cars. Used for degreasing surfaces before painting, cleaning painting tools and removing stains. For exterior and interior work.

Technical data

Density (DSTU ISO 2811-1)	0,85±0,04 g/cm ³
Warranty period	24 months, from the date of manufacturing.
Packaging	0,34 kg; 0,65 kg

Composition

A mixture of volatile organic compounds. Contains no precursors.

Application instruction

1 Using

The solvent shall be added to paint products with small portions, stirring thoroughly till required viscosity.

Use a wet cloth with the thinner for surface cleaning.

Cleaning of the tool: the dry product shall be removed from the tools after that poured thinner into metal receptacles and washed carefully the tool.

It is recommended to wash brushes and pollen brushes with detergent to keep safe the softness of the bristles.

SAFETY

Flammable! Keep away from fire! Keep in tightly closed original containers at the temperature from -20 °C till +40 °C. Keep out of moisture, direct sunlight, frost and out of reach of children. During application use personal safety gear (work clothes, rubber gloves, a respirator and safety glasses). If application is indoors well-arranged ventilation shall be provided. If skin contact, wash thoroughly with water and soap. If eye contact, rinse with plenty of running water. Consult a doctor if necessary. More detailed information you can read from the safety data sheet. The product has a sanitary-epidemical conclusion of the state expertise.

ENVIRONMENTAL PROTECTION

Do not empty into drains, ponds and in soil ! Liquid rests shall be delivered to the waste drop-off point. Rests of dry products and empty containers shall be recycled as common construction waste, in accordance with the Law.

The authenticity of this information is based on laboratory tests and practical knowledge. The quality of the product completely corresponds to the demands of TU U 20.3-33945998-005:2013. As a manufacturer, the company isn't responsible for the damage caused by application, which is not in accordance with the directions. The applicability of the product for specific purposes shall be defined entirely by the consumer. Current information loses validity with the issue of a new edition.

