

Odorless solvent

Specification

- it is without acrid smell
- it has a wide sphere of use
- it allows receiving paint product of required viscosity
- it evaporates from paint product at common air temperature



Sphere of application

Odorless solvent (without strong odor) is used as an analog of white spirit for diluting of enamels, varnishes, primers, oily paints, dried oils, bitumen, and other solvent organic-based materials, and also for the cleaning of tools, degreasing of metal and other surfaces. **Do not use for waterborne products!**

Technical data

Density (DSTU ISO 2811-1)	about 0,785 g/cm ³
Warranty period	24 months from the date of manufacturing.
Packaging	0,36kg (≈ 0,5l), 8kg (≈ 11l)
Color	colorless.

Composition

Odorless liquid hydrocarbons.

Application instruction

1 Using

The solvent shall be added to paint products with small portions, stirring thoroughly till required viscosity.

Use a wet cloth with the solvent for surface cleaning.

Cleaning of the tool: the dry product shall be removed from the tools after that poured solvent into metal receptacles and washed carefully the tool.

It is recommended to wash brushes and pollen brushes with detergent to keep safe the softness of the bristles.

SAFETY

Keep away from fire! Keep in tightly closed original containers at the temperature from -20 °C till + 40 °C. Keep out of moisture, direct sunlight and food. Keep in the places out of reach of children. During application use personal safety gear (work clothes, rubber gloves, a respirator and safety glasses). Provide well-arranged ventilation of the space. If skin contact, wash thoroughly with water and soap. If eye contact, rinse with plenty of running water. Consult a doctor if necessary. More detailed information you can read in the safety data sheet. The product has a sanitary-epidemical conclusion of the state expertise.

ENVIRONMENTAL PROTECTION

Do not empty into drains, ponds and in soil ! Liquid rests shall be delivered to the waste drop-off point. Rests of dry products and empty containers shall be recycled as common construction waste, in accordance with the Law.

The authenticity of this information is based on laboratory tests and practical knowledge. The quality of the product completely corresponds to the demands of TU U 24.3-32318370-012:2011. As a manufacturer, the company isn't responsible for the damage caused by application, which is not in accordance with the directions. The applicability of the product for specific purposes shall be defined entirely by the consumer. Current information loses validity with the issue of a new edition.

