

## Solvent for enamels, varnishes and paints (white spirit analogue)

### Specification

- wide sphere for application
- it allows receiving appropriate viscosity of paint products
- it evaporates from a paint material at the moderate temperatures of the environment



### Sphere of application

It is used as an analog of white spirit for dilution of enamels, varnishes, primers, oily paints, dry oil, bitumen products and for cleaning of tools, degreasing of metal and other surfaces.

### Technical data

Density (DSTU ISO 2811-1)	ab. 0,73 g/cm <sup>3</sup>
Warranty period	24 months from the date of manufacturing.
Packaging	0,5 l, 0,85 l
Color	colorless.

### Composition

A mix of hydrocarbon. It does not consist of precursors.

## Application instruction

### Using

The thinner shall be added to a paint material with small portions, stirred thoroughly till necessary viscosity.

Use clean cloth, sponge or brush wet with thinner for degreasing.

Working tools shall be cleaned with small portions of thinner and then, if necessary, with warm water and detergents.

### SAFETY

Flammable! Keep away from fire! Keep in tightly closed original containers at the temperature from -20 °C till +40 °C. Keep out of moisture, direct sunlight, frost and out of reach of children. During application use personal safety gear (work clothes, rubber gloves, a respirator and safety glasses). If application is indoors well-arranged ventilation shall be provided. If skin contact, wash thoroughly with water and soap. If eye contact, rinse with plenty of running water. Consult a doctor if necessary. More detailed information you can read from the safety data sheet. The product has a sanitary-epidemical conclusion of the state expertise.

### ENVIRONMENTAL PROTECTION

Do not empty into drains, ponds and in soil! Liquid rests shall be delivered to the waste drop-off point. Rests of dry products and empty containers shall be recycled as common construction waste, in accordance with the Law.

The authenticity of this information is based on laboratory tests and practical knowledge. The quality of the product completely corresponds to the demands of TU U 24.3-32318370-012:2011. As a manufacturer, the company isn't responsible for the damage caused by application, which is not in accordance with the directions. The applicability of the product for specific purposes shall be defined entirely by the consumer. Current information loses validity with the issue of a new edition.

